

UniFi UISP Branding

Q

Search UniFi products

Switching WiFi Camera Security Door Access CloudKeys & Gateways Power Tech Inte


Utility > Ultra 60W

Datasheet

In The Box

Marketing Images

Installation Guide



Overview

Dimensions	203 x 76 x 33 mm (8 x 3 x 1.3")
Port Layout	
1 GbE RJ45	8 (7 PoE+; 1 PoE++ input)
Max. PoE Output	Up to PoE+
Total PoE Availability	PoE++ input: 42W PoE+ input: 16W 60W PoE adapter input: 42W 60W AC adapter input: 52W 210W AC adapter input: 202
Form Factor	Compact desktop, wall, magnetic

Performance

Switching Capacity	16 Gbps
Total Non-Blocking Throughput	8 Gbps

Forwarding Rate	12 Mpps
-----------------	---------

Supported VLANs	256
-----------------	-----

MAC Address Table Size	4,000
------------------------	-------

^ Layer 2 Features

STP & RSTP	✓
------------	---

Egress Rate Limit	✓
-------------------	---

Flow Control	✓
--------------	---

Storm Control	✓
---------------	---

Multicast & Broadcast Rate Limiting	✓
-------------------------------------	---

Port Isolation	✓
----------------	---

Port Mirroring	✓
----------------	---

Jumbo Frames	✓
--------------	---

Loop Protection	✓
-----------------	---

^ Hardware

PoE Ports

PoE+	7
------	---

PoE++	1
-------	---

Max. PoE Wattage per Port by PSE

PoE+	30W
------	-----

Max. Power Consumption	9W (Excluding PoE Output) with PoE input 8W (Excluding PoE Output) with adapter input 210W (Including PoE Output) with 210W AC adapter input
------------------------	--

Power Method	(1) AC/DC adapter (Included) (1) PoE++
--------------	---

Power Input Method	DC Input PoE
--------------------	-----------------

Power Supply	AC/DC, external, 60W
--------------	----------------------

Supported Voltage Range	50—57V DC/PoE
-------------------------	---------------

Management	Ethernet
------------	----------

Heat Dissipation (Excluding PoE Output)	30.708 BTU/hr 27.296 BTU/hr
---	--------------------------------

Weight	Device: 320 g (11.3 oz)
	Wall mount: 45 g (1.6 oz)
	Adapter: 330 g (11.6 oz)
Enclosure Material	Polycarbonate
Ambient Operating Temperature	PoE++ input: -30 to 60° C (-22 to 140° F)
	60W AC adapter input: -20 to 45° C (-4 to 113° F)
Ambient Operating Humidity	10 to 90% noncondensing
Certifications	CE, FCC, IC

Stay in Touch

Email

Subscribe



[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2025 Ubiquiti, Inc. All rights reserved.